

Teboil 2T Bike

Teboil 2T Bike is fully synthetic 2-stroke engine oil.

Applications

Teboil 2T Bike is designed for use in powerful air- and water cooled motorcycles, mopeds, scooters and chainsaws. Oil is mixed with fuel as engine manufacturer recommends. It can also be used in oil injection systems.

Performance features and benefits

Oil has excellent lubrication and anti-wear properties, which makes it suitable for use in powerful and heavily loaded 2-stroke engines. It reduces exhaust smoke and delivers outstanding protection and cleanliness.

Typical physical characteristics

Teboil 2T Bike		Unit	Method
Density @ 20 °C	850	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	51	mm ² /s	ASTM D 445
Viscosity @ 100 °C	8,3	mm ² /s	ASTM D 445
Viscosity @ -20 °C	2270	mm ² /s	ASTM D 445
Viscosity @ -30 °C	7100	mm ² /s	ASTM D 445
Viscosity index	159		ASTM D 2270
Flash point	110	°C	ASTM D 92
Pour point	-42	°C	ASTM D 97

Specifications and approvals

API TC; JASO FD; ISO-L-EGD; ISO-L-GD++
Husqvarna, Piaggio Hexagon

[LLK Finland Oy reserves the right for changes](#)

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 19.7.2010

Postal address
PL 102
00121 Helsinki

Address
Bulevardi 26
01200 Helsinki

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2