

Teboil 2T Mix

Teboil 2T Mix is mineral oil based 2-stroke engine oil.

Applications

2T Mix is designed for use in air- and water cooled motorcycles, mopeds, scooters and chainsaws. Oil is mixed with fuel as engine manufacturer recommends. It can also be used in oil injection systems.

Performance features and benefits

Oil has good lubrication properties and it is suitable for use in wide range of 2-stroke engines. 2T Mix guarantees stable fuel-oil-mixture even in cold conditions. Effective additives keeps engine clean and protects it against wear and corrosion.

Typical physical characteristics

Teboil 2T Mix		Unit	Method
Density @ 20 °C	870	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	32	mm ² /s	ASTM D 445
Viscosity @ 100 °C	6,0	mm ² /s	ASTM D 445
Viscosity @ -20 °C	2000	mm ² /s	ASTM D 445
Viscosity @ -30 °C	8850	mm ² /s	ASTM D 445
Viscosity index	134		ASTM D 2270
Flash point	110	°C	ASTM D 92
Pour point	-45	°C	ASTM D 97

Specifications and approvals

API TC

[LLK Finland Oy reserves the right for changes](#)

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 19.7.2010

Postal address
PL 102
00121 Helsinki

Address
Bulevardi 26
01200 Helsinki

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2