

Teboil 2T Power Mix

DESCRIPTION OF THE PRODUCT

2T Power Mix is high quality semi synthetic two stroke oil for scooters, mopeds, chain saws and other 2T engines. It is compatible even with engines equipped with catalytic converters. It protects the engine reliably against wear, burns clean helping to keep pistons, exhaust systems and spark plugs clean.



USE, BENEFITS AND FEATURES

- Semi-synthetic two stroke oil with reliable lubrication properties
- Especially for modern scooters and mopeds and other engines equipped with catalytic converters
- Protects the engine strongly against wear
- Very good detergency properties keeps the engine clean

SPECIFICATIONS

- API TC
- JASO FD
- ISO-L-EGD

TYPICAL PHYSICAL CHARACTERISTICS

2T Power Mix		Unit	Method
Density 20 °C	859	kg/m ³	ASTM D 4052
Viscosity 40 °C	44	mm ² /s	ASTM D 445
Viscosity 100 °C	7,6	mm ² /s	ASTM D 445
Viscosity -20 °C	2200	mPa.s	ASTM D 5293
Viscosity-index	140		ASTM D 2270
Flash point	125	°C	ASTM D 92
Pour point	- 40	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package. STORAGE: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

