

Teboil Diamond 5W-40

Teboil Diamond 5W-40 is high quality, fully synthetic long life motor oil for passenger cars and vans with gasoline or diesel engine.

Applications

Teboil Diamond 5W-40 is high quality, fully synthetic long life engine oil. It is recommended for use in many engines equipped with diesel particulate filters and other modern exhaust gas after treatment systems.

Performance features and benefits

Diamond 5W-40 protects engine against wear and keeps it clean during the whole drain interval. Because of excellent cold temperature features, Diamond 5W-40 succeeds to maintain its flow ability even in hard winter conditions and ensures engines optimal lubrication immediately from cold start.

Typical physical characteristics

Teboil Diamond	5W-40	Unit	Method
Density @ 20 °C	844	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	83	mm ² /s	ASTM D 445
Viscosity @ 100 °C	14,2	mm ² /s	ASTM D 445
Viscosity @ -30 °C	4500	mPa.s	ASTM D 5293
Viscosity index	175		ASTM D 2270
Flash point	230	°C	ASTM D 92
Pour point	-48	°C	ASTM D 97

Specifications and approvals

API SM, SL/CF; ACEA A3/B3/B4, C3
BMW LL-04, MB 229.31, Porsche, VW 502.00, 505.00

[LLK Finland Oy reserves the right for changes](#)

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 14.5.2010