

Teboil EP 75W-90

Teboil EP 75W-90 is fully synthetic API GL-4 level transmission oil for passenger cars and commercial vehicles.

Applications

Teboil EP 75W-90 is high performance, fully synthetic transmission oil for passenger cars and commercial vehicles when API GL-4 is required.

Performance features and benefits

Because of fully synthetic base oil, product has low pour point which guarantees that transmission operates smoothly even in cold temperatures. Effective EP additives give to the transmission strong protection against wear in high temperatures and under heavy load. Excellent cold temperature features improves drivetrain efficiency and fuel economy.

Typical physical characteristics

Teboil EP	75W-90	Unit	Method
Density @ 20 °C	858	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	83	mm ² /s	ASTM D 445
Viscosity @ 100 °C	14,0	mm ² /s	ASTM D 445
Viscosity @ -40 °C	30 000	mPa.s	ASTM D 2983-87
Viscosity index	174		ASTM D 2270
Flash point	180	°C	ASTM D 92
Pour point	-48	°C	ASTM D 97

Specifications and approvals

SAE 75W-90; API GL-4; MT-1; MIL-L-2105; ZF TE-ML 02B, 16A, 17A, 19A; MAN 341 Z-2, ML

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 27.7.2010

Postal address
PL 102
00121 Helsinki

Address
Bulevardi 26
01200 Helsinki

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2