

**Teboil EP 80W-90**

**Teboil EP 80W-90** is mineral oil based API GL-4 level transmission oil for passenger cars and commercial vehicles.

---

**Applications**

Teboil EP 80W-90 is suitable for use in passenger cars and commercial vehicles manual transmissions when API GL-4 is required.

**Performance features and benefits**

Oil contains effective additives against wear, oxidation and foaming. It guarantees transmissions optimal lubrication.

**Typical physical characteristics**

Teboil EP	80W-90	Unit	Method
Density @ 20 °C	885	kg/m <sup>3</sup>	ASTM D 4052
Viscosity @ 40 °C	133	mm <sup>2</sup> /s	ASTM D 445
Viscosity @ 100 °C	15,0	mm <sup>2</sup> /s	ASTM D 445
Viscosity @ -26 °C	100 000	mPa.s	ASTM D 2983-87
Viscosity index	115		ASTM D 2270
Flash point	200	°C	ASTM D 92
Pour point	-33	°C	ASTM D 97

**Specifications and approvals**

SAE 80W-90; API GL-4; ZF TE-ML 02A, 16A, 17A, 19A; MIL-L-2105

[LLK Finland Oy reserves the right for changes](#)

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 27.7.2010