

Teboil Fluid D

Teboil Fluid D is Dexron II -type automatic transmission oil.

Applications

Teboil Fluid D is Dexron II -type automatic transmission oil for both passenger cars and commercial vehicles. It can also be used in many power steering systems and other applications requiring this type of automatic transmission oil.

Performance features and benefits

Because of high quality base oil and additives, Fluid D has very good anti-wear and oxidation stability properties which protect automatic transmission against wear. Low pour point guarantees excellent flowing ability in low temperatures.

Typical physical characteristics

Teboil Fluid D		Unit	Method
Density @ 20 °C	862	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	38	mm ² /s	ASTM D 445
Viscosity @ 100 °C	7,5	mm ² /s	ASTM D 445
Viscosity @ -40 °C	38 000	mPa.s	ASTM D 2983-87
Viscosity index	165		ASTM D 2270
Flash point	190	°C	ASTM D 92
Pour point	-45	°C	ASTM D 97

Specifications and approvals

Dexron II; Allison C4; ZF TE-ML 03, 09, 014; ATF Type A Suffix A; Ford M2C-138-CJ, M2C-166-H; CAT TO-2; MB 236.2

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 28.4.2011

Postal address
PL 102
00121 Helsinki

Address
Bulevardi 26
01200 Helsinki

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2