

Teboil Fluid E

Teboil Fluid E is high quality, semi-synthetic Dexron IIIH -type automatic transmission oil.

Applications

Teboil Fluid E is high quality Dexron IIIH -type automatic transmission oil for both passenger cars and commercial vehicles. It can also be used in many power steering systems and other applications requiring this type of automatic transmission oil.

Performance features and benefits

Carefully selected base oils and additives gives to Fluid E very good anti-wear and oxidation stability properties which protect automatic transmission against wear. Oil has ability to maintain friction features even in high temperatures. Because of low pour point, oil has excellent flowing ability in low temperatures guaranteeing transmissions smooth operation.

Typical physical characteristics

Teboil Fluid E		Unit	Method
Density @ 20 °C	846	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	38	mm ² /s	ASTM D 445
Viscosity @ 100 °C	8,0	mm ² /s	ASTM D 445
Viscosity @ -40 °C	16 000	mPa.s	ASTM D 2983-87
Viscosity index	182		ASTM D 2270
Flash point	220	°C	ASTM D 92
Pour point	-48	°C	ASTM D 97

Specifications and approvals

Dexron IIIH; Ford Mercon; MB 236.1, -2, -5; MAN 339 Type Z-1, V-1, V-2; Allison C4, TES 389; ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A/B, 17C; CAT TO-2; Voith 55.6335, Volvo 97341

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 8.1.2013

Postal address
PL 57
01511 Vantaa

Address
Äyritie 20
01510 Vantaa

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2