

**Teboil Fluid ES-Max**

**Teboil Fluid ES-Max** is premium quality, fully synthetic Dexron IIIH -type automatic transmission oil for commercial vehicles.

**Applications**

Teboil Fluid ES-Max is fully synthetic, commercial vehicle automatic transmission fluid. It is specially designed for commercial vehicles maximal long drain intervals. It can also be used in power steering systems and other applications requiring this type of automatic transmission oil.

**Performance features and benefits**

Because of very high quality base oils and additives, the oil has excellent anti-wear-, oxidation stability- and anti-foaming properties. It guarantees smooth operation of transmission in heavy circumstances. Oil enables maximal long drain intervals defined by many transmission manufacturers.

**Typical physical characteristics**

Teboil Fluid ES-Max		Unit	Method
Density@15°C	838	kg/m <sup>3</sup>	ASTM D 4052
Density@20 °C	835	kg/m <sup>3</sup>	ASTM D 4052
Viscosity@40 °C	36	mm <sup>2</sup> /s	ASTM D 445
Viscosity@100 °C	7,6	mm <sup>2</sup> /s	ASTM D 445
Viscosity@-40 °C	7 510	mPa.s	ASTM D 2983
Viscosity index	181		ASTM D 2270
Flash point	230	°C	ASTM D 92
Pour point	-50	°C	ASTM D 97

**Specifications and approvals**

Dexron IID, IIIG, IIIH; Ford Mercon, Mercon V; Allison C-4, TES-295, TES-389; ZF TE-ML 04D, 09, 11A/B, 14B/C, 16L/M, 20B/C; Voith H55.6336.xx; MB 236.6; MAN 339 Type V-2, Z-2, Z-3; Volvo 97341

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 07.11.2014