

## Teboil Gold S 5W-40

**Teboil Gold S 5W-40** is fully synthetic motor oil for passenger cars and vans with gasoline or diesel engine.

### Applications

Teboil Gold S 5W-40 is fully synthetic engine oil for passenger cars and vans with gasoline or diesel engine. It is suitable for use in many manufacturers' engines.

### Performance features and benefits

Gold S 5W-40 has balanced viscosity features which ensure optimal engine lubrication in varying circumstances. High quality additives keeps engine clean from sludge and deposits.

### Typical physical characteristics

Teboil Gold S	5W-40	Unit	Method
Density @ 20 °C	845	kg/m <sup>3</sup>	ASTM D 4052
Viscosity @ 40 °C	82	mm <sup>2</sup> /s	ASTM D 445
Viscosity @ 100 °C	14,2	mm <sup>2</sup> /s	ASTM D 445
Viscosity @ -30 °C	4600	mPa.s	ASTM D 5293
Viscosity index	180		ASTM D 2270
Flash point	220	°C	ASTM D 92
Pour point	-45	°C	ASTM D 97

### Specifications and approvals

API SL/CF; ACEA A3/B3/B4

BMW LL-98; MB 229.3; GM-LL-B-025; Porsche; VW 502.00, 505.00

[LLK Finland Oy reserves the right for changes](#)

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 14.5.2010

**Postal address**  
PL 102  
00121 Helsinki

**Address**  
Bulevardi 26  
01200 Helsinki

**Phone**  
+358(0)204 7001

**Fax**  
(09) 643 865

**Internet pages**  
[www.teboil.fi](http://www.teboil.fi)

**Business ID**  
0114795-2