

Teboil Hypoid 75W-90

Teboil Hypoid 75W-90 is premium quality, fully synthetic API GL-4/5 level axle/transmission oil.

Applications

Teboil Hypoid 75W-90 is fully synthetic total driveline oil designed for both passenger cars and commercial vehicles. It is also suitable for use in manual transmissions, when API GL-4 or GL-5 is required.

Performance features and benefits

Hypoid 75W-90 contains effective EP additives, which guarantees excellent lubrication properties even under heavy use. Excellent cold temperature features improves drivetrain efficiency and fuel economy.

Typical physical characteristics

Teboil Hypoid	75W-90	Unit	Method
Density @ 20 °C	872	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	95	mm ² /s	ASTM D 445
Viscosity @ 100 °C	14,0	mm ² /s	ASTM D 445
Viscosity @ -40 °C	65 000	mPa.s	ASTM D 2983-87
Viscosity index	150		ASTM D 2270
Flash point	180	°C	ASTM D 92
Pour point	-45	°C	ASTM D 97

Specifications and approvals

SAE 75W-90; API GL-4, GL-5; MT-1; MIL-PRF-2105E; MAN 3343 SL; Scania STO 1:0; ZF TE-ML 02B, 05B, 12L/N, 16F, 17B, 19C, 21B

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 8.1.2013

Postal address

PL 57
01511 Vantaa

Address

Äyritie 20
01510 Vantaa

Phone

+358(0)204 7001

Fax

(09) 643 865

Internet pages

www.teboil.fi

Business ID

0114795-2