

Teboil Hypoid 80W-90

Teboil Hypoid 80W-90 is mineral oil based API GL-5 level axle/transmission oil.

Applications

Teboil Hypoid 80W-90 is axle oil for both passenger cars and commercial vehicles. It is also suitable for use in manual transmissions when API GL-5 is required.

Performance features and benefits

Hypoid 80W-90 contains effective EP additives and it has good lubrication and anti-wear properties in every circumstances. Because of wide operating temperature range, it is suitable for year around use.

Typical physical characteristics

Teboil Hypoid	80W-90	Unit	Method
Density @ 20 °C	888	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	133	mm ² /s	ASTM D 445
Viscosity @ 100 °C	15,0	mm ² /s	ASTM D 445
Viscosity -26 °C	100 000	mPa.s	ASTM D 2983-87
Viscosity index	115		ASTM D 2270
Flash point	196	°C	ASTM D 92
Pour point	-33	°C	ASTM D 97

Specifications and approvals

SAE 80W-90; API GL-5; MIL-L-2105D; ZF TE-ML 02B, 05A, 12L/M, 16B, 17B, 19B, 21A

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 8.1.2013