

**Teboil Hypoid SAE 85W-140**

**Teboil Hypoid SAE 85W-140** is mineral oil based API GL-5 level axle/transmission oil for commercial vehicles.

---

**Applications**

Teboil Hypoid SAE 85W-140 is mineral oil based commercial vehicle axle oil. It is suitable for use in transmissions, which require API GL-5 level oil. Many commercial vehicle manufacturers recommend this viscosity grade in axles working under very heavy load or equipped with planetary gears.

**Performance features and benefits**

Advanced base oils and additives of Hypoid 85W-140 guarantees excellent lubrication. Strong lubricating film lasts even under extreme heavy load.

**Typical physical characteristics**

Teboil Hypoid	85W-140	Unit	Method
Density@20 °C	905	kg/m <sup>3</sup>	ASTM D 4052
Viscosity@40 °C	359	mm <sup>2</sup> /s	ASTM D 445
Viscosity@ 00 °C	25,5	mm <sup>2</sup> /s	ASTM D 445
Viscosity@ -12 °C	100 000	mPa.s	ASTM D 2983-87
Viscosity index	93		ASTM D 2270
Flash point	212	°C	ASTM D 92
Pour point	-18	°C	ASTM D 97

**Specifications and approvals**

API GL-5; MIL-L-2105D; DC 235,0; MAN 342 M-1; VOLVO 97310; ZF TE-ML 05A, 07A, 16B/C/D, 17B, 19B

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 10.12.2013