

Teboil Hypoid LS 80W-90

Teboil Hypoid LS 80W-90 is GL-5 level limited slip axle oil.

Applications

Teboil Hypoid LS 80W-90 is limited slip axle oil for both passenger cars and commercial vehicles. It is suitable for use in many different type of limited slip applications.

Performance features and benefits

Hypoid LS 80W-90 contains friction modifier additives which make it suitable for use in Limited slip axle applications. Advanced anti-wear-, corrosion protection- and oxidation stability additives guarantees optimal lubrication.

Typical physical characteristics

Teboil Hypoid LS	80W-90	Unit	Method
Density @ 20 °C	895	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	133	mm ² /s	ASTM D 445
Viscosity @ 100 °C	15,0	mm ² /s	ASTM D 445
Viscosity @ -26 °C	120 000	mPa.s	ASTM D 2983-87
Viscosity @ -40 °C	115		ASTM D 2270
Viscosity index	180	°C	ASTM D 92
Flash point	-33	°C	ASTM D 97

Specifications and approvals

SAE 80W-90; API GL-5 (LS); MIL-L-2105D; ZF TE-ML 05C, 12C, 21C

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 28.4.2011

Postal address

PL 102
00121 Helsinki

Address

Bulevardi 26
01200 Helsinki

Phone

+358(0)204 7001

Fax

(09) 643 865

Internet pages

www.teboil.fi

Business ID

0114795-2