

**Teboil Moniaste 10W-30 and 15W-40**

**Teboil Moniaste** oils are mineral oil based multi-grade engine oils.

---

**Applications**

Teboil Moniaste oils are meant for older passenger cars and vans with gasoline or diesel engines without exhaust gas after treatment systems.

**Performance features and benefits**

Teboil Moniaste oils create thick lubricating film which prevents oil consumption and ensures optimal lubrication in every circumstance.

**Typical physical characteristics**

Teboil Moniaste	10W-30	15W-40	Unit	Method
Density @ 20 °C	876	882	kg/m <sup>3</sup>	ASTM D 4052
Viscosity @ 40 °C	70	101	mm <sup>2</sup> /s	ASTM D 445
Viscosity @ 100 °C	10,5	13,5	mm <sup>2</sup> /s	ASTM D 445
Viscosity @ -20 °C	-	6900	mm <sup>2</sup> /s	ASTM D 445
Viscosity @ -25 °C	6500	-	mm <sup>2</sup> /s	ASTM D 445
Viscosity index	140	130		ASTM D 2270
Flash point	210	220	°C	ASTM D 92
Pour point	-36	-33	°C	ASTM D 97

**Specifications and approvals**

API SF/CD

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 14.5.2010