

Teboil Monitra Plus 10W-30

Teboil Monitra Plus 10W-30 is multipurpose oil for farming machinery.

Applications

Teboil Monitra Plus 10W-30 is engine-, transmission-, axle- and hydraulic oil for farming machines. Because of carefully designed friction properties, Monitra plus is suitable for use in many wet brakes and power take-off clutches.

Performance features and benefits

Because of carefully designed friction properties, Monitra plus is suitable for use in many wet brakes and power take-off clutches. Oil is specially designed for demanding Finnish climate conditions and it guarantees machines reliability in every circumstances.

Typical physical characteristics

Teboil Monitra Plus	10W-30	Unit	Method
Density @ 20 °C	875	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	75	mm ² /s	ASTM D 445
Viscosity @ 100 °C	11,0	mm ² /s	ASTM D 445
Viscosity index	135		ASTM D 2270
Flash point	210	°C	ASTM D 92
TBN	9,5	mgKOH/g	ASTM D 4739
Pour point	-39	°C	ASTM D 97
Pumpability	-31	°C	ASTM D 4684

Specifications and approvals

API CG-4, CF-4, SF/CF; GL-4, GL-5; ACEA E3

Massey-Ferguson M1127, M1135, M1139, M1144; Case IH M1207; Ford M2C 86A, -134C/D, -159B; John Deere J 20A/C, J27; Allison C4; CAT TO-2; ZF TE-ML 06, -07, -12; MIL-L-2104D

[LLK Finland Oy reserves the right for changes](#)

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 28.4.2011

Postal address
PL 102
00121 Helsinki

Address
Bulevardi 26
0120 Helsinki

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2