

**Teboil MultiPurpose Grease**

**Teboil MultiPurpose Grease** is lithium thickened universal grease.

**Applications**

Teboil MultiPurpose Grease is universal lubrication grease that can be used in both automotive and industrial applications. The grease is suitable for use for wide range of plain and roller bearings under light or moderate load.

**Performance features and benefits**

MultiPurpose Grease contains antioxidants, corrosion inhibitors and anti-wear additives. The lubricating grease offers good mechanical stability and corrosion protection, making it suitable for bearing lubrication even in wet environments.

**Typical physical characteristics**

Teboil MultiPurpose Grease		Unit	Method
Thickener	Lithium		
Color	Yellowish-brown		
NLGI-grade	2		ASTM D 217
Penetration 60 strokes	280	1/10 mm	ISO 2137
Penetration 100 000 strokes	305	1/10 mm	ISO 2137
Dropping point	>180	°C	IP 396
Base oil viscosity @ 40 °C	110	mm <sup>2</sup> /s	ISO 12058
4-ball weld load	2000	N	DIN 51350:4
Corrosion protection			
SKF Emcor distilled water	0-0		ISO 11007
Copper corrosion 24h/100 °C	1b		ASTM D 4048
Water stability	1-90		DIN 51807/1
Lubrication ability			
SKF R2F Test A	Pass		SKF
SKF R2F Test B (120 °C)	Pass		SKF

**Specifications and approvals**

DIN 51502 K2K-30  
ISO 6743 ISO-L-XCCEA2

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 8.1.2013