

Teboil Pienkoneöljy

Teboil Pienkoneöljy is single grade engine oil for 4-stroke small engines.

Applications

Teboil Pienkoneöljy is designed for small 4-stroke engines like crass cutters and aggregators.

Performance features and benefits

Teboil Pienkoneöljy is SAE 30 viscosity grade single grade engine oil. Most of the small engine manufacturers recommend this viscosity grade engine oil use in their machines. It ensures engines optimal lubrication and keeps it clean.

Typical physical characteristics

Teboil Pienkoneöljy	30	Unit	Method
Density @ 20 °C	890	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	98	mm ² /s	ASTM D 445
Viscosity @ 100 °C	11,5	mm ² /s	ASTM D 445
Viscosity index	104		ASTM D 2270
Flash point	240	°C	ASTM D 92
Pour point	-24	°C	ASTM D 97

Specifications and approvals

API SJ, SF

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 19.7.2010

Postal address
PL 102
00121 Helsinki

Address
Bulevardi 26
0120 Helsinki

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2