

Teboil Super HPD 10W-30 and 15W-40

Teboil Super HPD 10W-30 and 15W-40 are mineral oil based commercial vehicle diesel engine oils for heavy use.

Applications

Teboil Super HPD 10W-30 and 15W-40 are designed for heavy commercial vehicle use. Oils are suitable for use in many European Euro 3 and Euro 4 engines and American diesel engines, which requires API CI-4.

Performance features and benefits

Oil has ability to keep engine clean and give ultimate protection against wear and bore polish. Oils have very good hot and cold temperature features which guarantees optimal lubrication in every circumstances.

Typical physical characteristics

Teboil Super HPD	10W-30	15W-40	Unit	Method
Density @ 20 °C	877	886	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	73	104	mm ² /s	ASTM D 445
Viscosity @ 100 °C	11,0	13,5	mm ² /s	ASTM D 445
Viscosity index	140	135		ASTM D 2270
Flash point	210	224	°C	ASTM D 92
TBN	10,00	10,00	mgKOH/g	ASTM D 4739
Pour point	-36	-33	°C	ASTM D 97
Pumpability	-30	-25	°C	ASTM D 4684

Specifications and approvals

API CI-4, CH-4, CG-4, CF-4; ACEA E7, E5, B3, B4
MB 228.3; MAN 3275; Mack EO-M Plus; RVI RLD; Volvo VDS-2, VDS-3; CAT ECF-1a, -2;
Global DHD-1; Cummins CES 20071,- 2, -6, -7, -8; Jaso DH-1; MTU 2

[LLK Finland Oy reserves the right for changes](#)

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 20.7.2010

Postal address
PL 102
00121 Helsinki

Address
Bulevardi 26
0120 Helsinki

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2