

Teboil Super HPD 10W-40

Teboil Super HPD 10W-40 is synthetic commercial vehicle diesel engine oil for heavy use.

Applications

Teboil Super HPD 10W-40 is designed for very heavy commercial vehicle use. Because of ACEA E7 and API CI-4 classifications, it can be used in most European and American low emission heavy duty diesel engines.

Performance features and benefits

Oil has ability to keep engine clean and give ultimate protection against wear and bore polish. It has high quality hot and cold temperature features which guarantees optimal lubrication in every circumstances.

Typical physical characteristics

Teboil Super HPD	10W-40	Unit	Method
Density @ 20 °C	866	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	100	mm ² /s	ASTM D 445
Viscosity @ 100 °C	14,5	mm ² /s	ASTM D 445
Viscosity index	152		ASTM D 2270
Flash point	234	°C	ASTM D 92
TBN	10,0	mgKOH/g	ASTM D 4739
Pour point	-39	°C	ASTM D 97
Pumpability	-32	°C	ASTM D 4684

Specifications and approvals

API CI-4, CH-4, CG-4, CF-4; ACEA E7, E5, B3, B4
MB 228.3; MAN 3275; Mack EO-M Plus; RVI RLD; Volvo VDS-2, VDS-3; CAT ECF-1a, -2;
Global DHD-1; Cummins CES 20071,- 2, -6, -7, -8; Jaso DH-1; MTU 2

[LLK Finland Oy reserves the right for changes](#)

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 20.7.2010

Postal address
PL 102
00121 Helsinki

Address
Bulevardi 26
0120 Helsinki

Phone
+358(0)204 7001

Fax
(09) 643 865

Internet pages
www.teboil.fi

Business ID
0114795-2