

Teboil Super XLD XLD-3 10W-40

DESCRIPTION OF THE PRODUCT

Super XLD-3 10W-40 is very high quality fully synthetic heavy duty diesel engine oil for heavy loads and demanding driving conditions. The oil is suitable for many brands, but it is specially developed for Scania Euro 1–6 engines.

It has very diverse performance specifications and therefore it is suitable also for many different engines made by various engine manufacturers.

USE, BENEFITS AND FEATURES

- Very efficient cleaning capacity keeps engine clean even in hardest driving conditions.
- Excellent viscosity behavior eases cold starts and gives improved protection to hot and heavily loaded engine.
- Boosted additive technology maintains the cleaning abilities and prevents formation of soot induced sludge on long drain intervals.
- Forms strong lubricating film on the components of engine and ensures reliable lubrication even in most demanding use.

SPECIFICATIONS

- API CF
- ACEA E7, E4
- Scania LDF-3
- MB 228.5
- MAN M3277
- Volvo VDS-3
- Renault RXD, RLD-2
- Deutz DQC IV-05/10
- MTU Type 3

TYPICAL PHYSICAL CHARACTERISTICS

	10W-40	Yksikkö	Menetelmä
Density 20 °C	863	kg/m ³	ASTM D 4052
Viscosity 40 °C	85	mm ² /s	ASTM D 445
Viscosity 100 °C	12,9	mm ² /s	ASTM D 445
Viscosity-index	151		ASTM D 2270
Flash point	240	°C	ASTM D 92
TBN	16,4	mgKOH/g	ASTM D 4739
Pour point	-42	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package. STORAGING: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

