

**Teboil Super XLD EEV 10W-40**

**Teboil Super XLD EEV** is fully synthetic heavy duty diesel engine oil for very low emission engines.

**Applications**

Teboil Super XLD EEV 10W-40 is fully synthetic commercial vehicle diesel engine oil for very low emission Euro 5, 6 and EEV - engines. These types of engines are equipped with very advanced exhaust gas after treatment systems.

**Performance features and benefits**

Oil is manufactured from the best synthetic base oils and advanced additives. Oils phosphorous, sulfur and sulfate ash content is very low. Because of this new technology, oil protects cylinders against bore polish and prevents sludge formation ensuring optimal function of exhaust gas after treatment systems.

**Typical physical characteristics**

| Teboil Super XLD EEV | 10W-40 | Unit               | Method      |
|----------------------|--------|--------------------|-------------|
| Density @ 20 °C      | 857    | kg/m <sup>3</sup>  | ASTM D 4052 |
| Viscosity @ 40 °C    | 85     | mm <sup>2</sup> /s | ASTM D 445  |
| Viscosity @ 100 °C   | 12,9   | mm <sup>2</sup> /s | ASTM D 445  |
| Viscosity index      | 151    |                    | ASTM D 2270 |
| Flash point          | 235    | °C                 | ASTM D 92   |
| TBN                  | 11,70  | mgKOH/g            | ASTM D 4739 |
| Pour point           | -36    | °C                 | ASTM D 97   |
| Pumpability          | -30    | °C                 | ASTM D 4684 |

**Specifications and approvals**

API CI-4; ACEA E7, E6, E4  
Scania LA; MB 228.51; MAN 3477; Volvo VDS-3; Renault RLD, RLD-2, RXD; DAF Extended Drains; CAT ECF-1a; Jaso HD-2

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 8.1.2013