

**Teboil Ward L 20T SAE 30 and 40****Applications**

Teboil Ward L 20T SAE 30 and 40 are cylinder- and system oils for medium speed trunk-piston engines.

**Performance features and benefits**

Ward L 20T is intended for use in engines which are using fuels with less sulphur than < 2,0 %.

**Typical data**

<b>Teboil Ward L 20T</b>	<b>30</b>	<b>40</b>	<b>Unit</b>	<b>Method</b>
Density @ 20 °C	897	902	kg/m <sup>3</sup>	ASTM D 4052
Viscosity @ 40 °C	110	150	mm <sup>2</sup> /s	ASTM D 445
Viscosity @ 100 °C	12,0	14,5	mm <sup>2</sup> /s	ASTM D 445
Viscosity index	98	96		ASTM D 2270
Flash point	240	245	°C	ASTM D 92
Pour point	-18	-12	°C	ASTM D 97
TBN	20,0	20,0	mgKOH/g	ASTM D 4739
Sulphated ash	2,6	2,6	p%	ASTM D 874

**Performance**

SAE 30 and 40

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 28.4.2011

**Postal address**  
PL 102  
00121 Helsinki

**Address**  
Bulevardi 26  
01200 Helsinki

**Phone**  
+358(0)204 7001

**Fax**  
(09) 643 865

**Internet pages**  
[www.teboil.fi](http://www.teboil.fi)

**Business ID**  
0114795-2