

Teboil Ward L 10T SAE 30 and 40

Applications

Teboil Ward L 10T SAE 30 and 40 are cylinder- and system oils for medium speed trunk-piston engines.

Performance features and benefits

Ward L 10T is intended for use in engines which are using fuels with less sulphur than < 1,5 %.

Typical data

Teboil Ward L 10T	30	40	Unit	Method
Density @ 20 °C	898	899	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	106	145	mm ² /s	ASTM D 445
Viscosity @ 100 °C	11,5	14,3	mm ² /s	ASTM D 445
Viscosity index	95	96		ASTM D 2270
Flash point	230	255	°C	ASTM D 92
Pour point	-12	-12	°C	ASTM D 97
TBN	12,2	12	mgKOH/g	ASTM D 4739
Sulphated ash	1,59	1,60	p%	ASTM D 874

Performance

SAE 30 and 40

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 28.4.2011

Postal address

PL 57
01511 Vantaa

Address

Äyritie 20
01510 Vantaa

Phone

+358(0)204 7001

Fax

(09) 643 865

Internet pages

www.teboil.fi

Business ID

0114795-2