

Teboil Wetol

Teboil Wetol is transmission and axle oil for machines equipped with wet brakes.

Applications

Teboil Wetol is universal tractor transmission oil (UTTO) and has been developed for the hydraulics and transmission systems of tractors and other machines equipped with wet brakes. It is suitable for use in applications which use same oil in transmissions, axles and hydraulics.

Performance features and benefits

In oils special features has been carefully considered anti-wear properties and smooth and noiseless operation of wet brakes.

Typical physical characteristics

Teboil Wetol	80	Unit	Method
Density @ 20 °C	882	kg/m ³	ASTM D 4052
Viscosity @ 40 °C	69	mm ² /s	ASTM D 445
Viscosity @ 100 °C	11,0	mm ² /s	ASTM D 445
Viscosity @ -26 °C	50 000	mPa.s	ASTM D 2983-87
Viscosity index	150		ASTM D 2270
Flash point	210	°C	ASTM D 92
Pour point	-39	°C	ASTM D 97

Specifications and approvals

SAE 80 LS; SAE10W-30; API GL-4; ISO VG68; HLPD/HVLPD; Allison C4; CAT TO-2; Case NH CNH MAT 3505, 3509, 3525; Case MS B6, 1206, 1207; Ford ESN-M2C 86B/C, 134D, FNHA-2-C-200.00; John Deere J20C; Kubota UDT Fluid; MF CMS M 1100, 1127A/B, 1141, 1143, 1145; VCE WB 101; ZF TE-ML 03E, 05F, 06K, 17E, 21F

Technical data is based on approximate measures. Due to continual product research and development, the information contained herein is subject to change without notification. 28.4.2011